



NOTE
 DURING EXCAVATION, MINIMIZE DISTURBING THE GROUND AROUND TRENCH AS MUCH AS IS FEASIBLE, AND SMOOTH SURFACE FOLLOWING EXCAVATION TO AVOID CONCENTRATING FLOWS. COMPACTION MUST BE ADEQUATE TO PREVENT UNDERCUTTING FLOWS.

TYPICAL INSTALLATION DETAIL
 (STEEL POSTS SHOWN)



TYPICAL HIGH VISIBILITY SILT FENCE WITH BACKUP SUPPORT ISOMETRIC
 (STEEL POSTS SHOWN)



SPLICED FENCE SECTIONS SHALL BE CLOSE ENOUGH TOGETHER TO PREVENT SILT LADEN WATER FROM ESCAPING THROUGH THE FENCE AT THE OVERLAP.

SPLICE DETAIL
 (STEEL POSTS SHOWN)

NOTES

1. Angle high visibility silt fence terminal end uphill 24" (in) to 48" (in) to prevent sediment from flowing around the end of the fence.
2. Perform maintenance in accordance with **Standard Specification, Sections 8-01.3(9)A and 8-01.3(15)**.
3. Splices shall never be placed in low spots or sump locations. If splices are located in low or sump areas, the fence may need to be reinstalled unless the Project Engineer approves the installation.
4. Install silt fencing parallel to mapped contour lines.



HIGH VISIBILITY SILT FENCE WITH BACKUP SUPPORT
STANDARD PLAN I-30.16-01

SHEET 1 OF 1 SHEET
 APPROVED FOR PUBLICATION

DRAWN BY: BILL BERENS