



King County

Meadowbrook Bridge Rehabilitation

Technical Session Agenda

Introduction & Program Design (Jessy Jose, King County)

- a. Project Location & Bridge Background
- b. Structural and Functional Deficiencies
- c. Project Planning and Evaluation
- d. Bridge Rehabilitation Goals

Rehabilitation Design & Construction (Ken Wilson, ISE)

- a. Design Development General Requirements
- b. Structural Component Details
- c. Construction Sequence
- d. Construction Photos
- e. Conclusion

Q&A



King County



Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



- Located in East King County
- 1,900 ADT



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Meadowbrook Bridge looking North

- Built in 1921
- Posted for load limit due to structural deficiencies (16 Ton)
- Narrow bridge width (18'-6").
- Substandard vertical alignment with limited sight distance
- Posted Vertical clearance only 14'
- Very Low sufficiency rating (4.27/SD)



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Meadowbrook Bridge looking
West- Down stream



Timber Approach

- 9 approach timber trestle spans
- 220' truss main span
- 6" of flood clearance above 100 year flood elevation



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



King County
Historic Landmark
– 1921 opening
ceremony





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



LOOKING NORTH



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



**LOOKING WEST- Poor sight distance
and substandard horizontal curve**



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Asphalt Deck
Deterioration



Corroded Lateral
Support

Approach cracks



Corroded Sidewalk
Support



Structural Deficiencies



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Weak Substandard
Bridge Rails



Poor Drainage
Details/Bottom
Cord Corrosion





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Damaged top lateral
due to high load hit –
14' Vertical clearance





King County


Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion




Split stringers

Main Span Timber Stringers



Summary of Deficiencies



- Low SR and SD
- Seismically Vulnerable- Liquefiable soil
- Load Limited
- Narrow Travel Way Width
- Substandard/Deteriorated Rails
- Low Flood Clearance
- Poor Sight distance

Added Constraint:

- Historical - King County Landmark



King County


Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion





Project Goals

- **Improve Traffic Safety**
 - Lane & shoulder width as well as sight distance
 - Upgrade rail capacity and transitions to current standards
- **Reduce frequent maintenance needs**
 - Aging structure and paint system
- **Remove bridge load posting**
 - Provide adequate capacity for all legal truck loads
- **Eliminate Structural Deficiencies**
 - Timber Approach Capacity
 - Main Span Stringers
 - Steel Truss and Floorbeam Capacity
 - Bridge rail capacity and configuration deficiency
- **Seismically retrofit the bridge**
 - Reduce foundation demands and mitigate liquefiable soil
- **Preserve King County Landmark**
 - Retain the existing truss in current vehicular bridge usage



King County

Meadowbrook Bridge Rehabilitation

Rehabilitation Design & Construction

- a. Design Development**
- b. Structural Details**
- c. Construction Sequence & Photos**
- d. Conclusions**



Design Requirements

1. Eliminate Structural Deficiency
2. Seismically retrofit the bridge
3. Replace the bridge rail
4. Improve traffic safety for lane widths and sight distance
5. Improve flood clearance
6. Bring vertical clearance to standard
7. Improve frequent maintenance Demands
8. Preserve King County Landmark

Design Solutions

- 1a. Replace timber approach spans
- 1b. Reduce main truss demand (one lane bridge)
- 1c. Replace truss deck with light weight system
- 1d. Strengthen floorbeams through composite action
- 2a. Improve liquefiable soils
- 2b. Isolate/minimize truss substructure response
- 3a. Replace/add bridge rails and missing transitions
- 4a. Add roadway shoulders and increase lane widths
- 4b. Convert truss to one lane with signal actuation
- 4c. Added stop bars and “Rest-in-Red” signaling to slow traffic and improving sight distance
- 5a. Reducing truss deck thickness and raised bridge
- 6a. Thinner replacement deck improved clearance
- 7a. Replace the aging deck and timber trestles
- 7b. Remove the existing lead paint and repaint
- 7c. Collect truss drainage and provide treatment
- 8a. Retain the existing truss for vehicular usage
- 8b. Actions per Certificate of Appropriateness



King County

Meadowbrook Bridge Rehabilitation


Introduction

Design Development

Construction

Conclusion

Rehabilitation Comparison



EXISTING BRIDGE SECTION

REHABILITATED BRIDGE SECTION





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

One Lane Traffic Configuration

Current ADT
:1900

20 year
forecasted
ADT :4500



Analysis: 15.1
sec delay
during
peak



King County

Meadowbrook Bridge Rehabilitation


Introduction

Design Development

Construction

Conclusion

Final Design Configuration





King County

Meadowbrook Bridge Rehabilitation


Introduction

Design Development

Construction


Conclusion

STAGE 1 (REMOVE APPROACH TRETTLES AND TRUSS DECK)




1. RELOCATE WATER LINE VIA DIRECTIONAL BORING.
2. RELOCATE OH POWER.
3. INSTALL TEMPORARY BOTTOM TRUSS BRACING AND DEBRIS CONTAINMENT SYSTEM.
4. CLOSE BRIDGE. REMOVE EXISTING TRUSS DECK SYSTEM.
5. DEMOLISH BOTH THE NORTH AND SOUTH APPROACH TIMBER TRETTLES.
6. BEGIN RELOCATION OF SANITARY SEWER BELOW SOUTH APPROACH.

STAGE 2 (SOIL DENSIFICATION AND PILE DRIVING)





1. LOCATE AND STAKE NEW PILES.
2. AT SOUTH APPROACH PLACE STONE COLUMN ROW "B".
3. COMPLETE RELOCATION OF THE EXISTING SANITARY SEWER.
4. INSTALL COMPACTION GROUT COLUMNS TO PROTECT THE EXISTING MAIN TRUSS PIERS.
5. PLACE STONE COLUMN ROW "A" AND CONTINUE STONE COLUMN PLACEMENT WORKING AWAY FROM THE RIVER.
6. PLACE NORTH APPROACH COMPACTION GROUTING THEN STONE COLUMNS BEGINNING AT THE RIVER AND WORKING AWAY.
7. DRIVE PILING.

STAGE 3 (TRUSS REPAIR AND PAINTING)





1. REPAIR TRUSS MEMBERS AND SIDEWALK SUPPORTS.
2. INSTALL NEW STEEL STRINGERS BETWEEN FLOORBEAMS.
3. SET UP NEGATIVE PRESSURE CONTAINMENT SYSTEM (4 PANEL MAX AT A TIME), PREPARE SURFACES, AND PAINT THE BRIDGE.
4. MOVE NEGATIVE PRESSURE CONTAINMENT & CONTINUE OPERATION.
5. FORM SOUTH APPROACH STRUCTURES.

STAGE 4 (JACK TRUSS, REPLACE BEARINGS, AND CONSTRUCT DECK SYSTEM)



1. JACK UP TRUSS, CONSTRUCT CONCRETE PEDESTALS, AND REPLACE TRUSS BEARINGS.
2. CONSTRUCT SOUTH APPROACH STRUCTURES.
3. INSTALL TRUSS DECK SYSTEM AND CURBS.
4. RECONSTRUCT TIMBER SIDEWALK DECKING AND RAMPS.
5. PLACE STRUCTURAL EARTH WALLS.

STAGE 5 (COMPLETE APPROACH SPANS AND ROADWAY)



1. CONSTRUCT NORTH APPROACH STRUCTURES.
2. CAST APPROACH CONCRETE CURB & INSTALL METAL RAILING.
3. CONSTRUCT DRAINAGE STRUCTURES AND STORM WATER WETLAND.
4. CONSTRUCT APPROACH SLABS AND APPROACH ROADWAY.
5. INSTALL APPROACH RAILS AND TERMINALS.
6. INSTALL TRAFFIC SIGNALS, PERMANENT SIGNS, AND ILLUMINATION.
7. COMPLETE PAINT LINES AND OPEN BRIDGE TO TRAFFIC.
8. FINISH LANDSCAPING, PLANTING, AND REMOVE TESC.



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Water Line Directional Boring Relocation





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Installing Temporary Work Platforms





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Demolition Work





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Heat Straightening Truss Repairs





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Grout Compaction Soil Densification





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Stone Column Soil Densification & Monitoring





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Painting Work





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Approach Pile Driving





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Approach Work





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Truss Deck Replacement Work





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Truss Lifting/Bearing Work





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Exodermic Truss Deck Replacement





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Signal Installation





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Bridge Rail Installation





King County


Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Construction Cost

- \$4,152,000

Construction Duration

- 7 1/2 months



King County


Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Before

After





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Before



After



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Before



After





King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion



Before



After



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction


Conclusion





Conclusion

- ✓ Complied with COA from King County Landmark
- ✓ Cost Effective Relative to Replacement Bridge Costs
- ✓ Prolonged Structure's Useful Life
- ✓ Enhanced Public Safety and Welfare
- ✓ Environmental Benefits and Historic Compatibility



	Original Bridge	Rehabilitated Bridge
Lane Width	9 feet	12 feet
Vertical Clearance	14 feet (as posted)	16 feet 6 inches
Legal Load	16 Tons	25 Tons
Flood Clearance	~6 inches	~2 feet
Maintenance	High	Low
Traffic and Pedestrian Rails	Not to Standard	Meets Standards
Seismic Safety	Vulnerable	Upgraded
Water Quality	No Treatment	Full Treatment



King County

Meadowbrook Bridge Rehabilitation

Introduction

Design Development

Construction

Conclusion

Acknowledgements

Owner/Client: KING COUNTY

Bridge & Structures

Jim Markus, Managing Engineer
Stephen Jiang, Structural Engineer
Jessy Jose, P.E, Project Manager

Construction

Bob Lee, Supervisor
Kino Gomez, Resident Engr.
Casey Hayes, Inspector

Contractor:

Wilder Construction

Phil Bogardus, PM
Vance Aeschleman, Superint.

Consultant:

ABKJ, Inc.

Pong Jongjitirat, PIC
Jim Morris, Engineer

Ken Wilson P.E, S.E, Project
Engr./Manager, Currently with Integrity
Structural Engineering, PLLC





King County

Meadowbrook Bridge Rehabilitation

Q & A

