

Innovative and Sustainable Bridge Solution using Recycled Plastic Composites



Western Bridge Engineers Seminar

By

Vijay Chandra, PE, Director of Structures, Parsons Brinckerhoff

John S. Kim, PhD, PE, Supervising Engineer, Parsons Brinckerhoff



September 2011

From Wasteful to Useful



What is Thermoplastic?

- **Recycled Plastic**
- **Immiscible Polymer Blend**
 - ❖ **High Density Polyethylene with Polystyrene or Polypropylene coated glass fibers (up to 8%)**




Product Advantages

- ▲ **Green Product (Recycled Plastic)**
- ▲ **No Corrosion, Rotting or Insect Infestation**
- ▲ **Reduced Landfill Dumping**
- ▲ **Good toughness Characteristics**
- ▲ **No Chemical additives**
- ▲ **Green House Gas Savings**
- ▲ **Reduced Maintenance**
- ▲ **Sustainable & Durable**
- ▲ **Cost Competitive: Initial and Life Cycle**

Thermoplastic Properties

- **Weight: 55pcf (Wood: 60pcf; Concrete: 150pcf; Steel: 490pcf)**
- **Specific Gravity: 0.85 – 0.90**
- **Elastic Modulus: 250,000 psi**
- **Allowable Flexural Stress: 600 psi (Ult. = 3,000 psi)**
- **Allowable Compressive Stress: 600 psi (Ult. = 2,500 to 4,300 psi)**
- **Allowable Shear Stress: 350 psi (Ult. = 1,500 psi)**
- **Coefficient of Thermal Expansion: 0.0000282 in/in/deg F**

Typical Stress/Strain Curve



Design Considerations

- Ultraviolet Degradation - 0.003 in/yr (full sunlight)
- Creep - Low (high Safety factor to Ultimate)
- Thermal Resistance - Heat Deflection +/- 250 deg F
- Skid Resistance - Coefficient Of Friction = 0.5 with tire
- Acid Resistance - To most acids & salts
- Moisture Absorption - Virtually impervious
- Abrasion - High resistance to sand & salts
- Color - Graphite



Bridge Applications

Fort Leonard Wood, MO



1998

W = 26 ft; L = 24 ft

Max Load = 25,000 lbs.

Wharton State Forest, NJ

- * 2002
- * Length - 56 feet
- * Live Load - HS 20



Fort Bragg, NC



Load Bearing Capability



M1 Abrams Tank on the Bridge


Fort Eustis, VA

Bridges 3 and 7

- **Live Load: Cooper E60 and 260 Kip alternate loading with 20% impact**
- **Deflection: $L/600$**
- **Length of Piles: about 45 feet**
- **Capacity of piles: 17 – 20 tons in end bearing per Pile**
- **Abutments: Existing timber abutments retained**
- **RSPC Elements: Railroad Ties, Curbs, Girders, Shear Blocks, Pier Caps, Piles and Transverse Connectors**

Fort Eustis, VA


Bridge No. 3



ELEVATION

Fort Eustis, VA


Bridge No. 7



ELEVATION

Fort Eustis, VA

Typical Section



Fort Eustis Construction



Driving



Splicing



Pile Cap Installation

Fort Eustis Construction



Transportation



Storage



Installation

Fort Eustis, VA

Completed Bridge No. 3



Fort Eustis, VA

Completed Bridge No. 7



Fort Eustis, VA

Live Loads for Testing



Fort Eustis, VA Deflections



Estimated Deflection = 0.25"

Measured Deflection = 0.21"

Bridge No. 3

Estimated Deflection = 0.32"


Measured Deflection = 0.29"



Bridge No. 7

Other Applications



County Highway Bridge



Other Applications

- **Marinas**
- **Fenders**
- **Jetties and Piers**
- **Platforms and Boardwalks**
- **Temporary Reusable Bridges**
- **Sound Walls & Retaining Walls**
- **Railroad Ties & Switch Sets**

Retaining Walls



Railroad Ties and Switch Set



**Installation by Washington, DC Metro
Switch Set**

Conclusion

- **Green, Sustainable and Durable**
- **Environmentally Beneficial**
- **Vast Areas of Application**
- **Accelerated Construction**
- **Minimal Maintenance**
- **Cost Competitive**


Acknowledgements



- ❖ Producer: Axion International, Inc.
- ❖ Inventor: Rutgers University
- ❖ Designer: Parsons Brinckerhoff
- ❖ Marketer: Innovative Green Solutions



Questions?



World's 1st Airplane
12 seconds
120 ft distance



World's 1st Plastic Railroad Bridges
12 ft max. span
120 ft total length