

SR 520 Bridge Replacement Program

Test Pile Project Results

Presented by
Paul Bott P.E., S.E.
HDR Engineering Inc.





Agenda

- Introduction
- In-Water Work Activities
- Test Pile Project Objectives
- Noise Reduction Results
- In-water Work Windows
- Lateral Load Test Results









Introduction

- \$4.65B Project
- Enhance Safety and Reliability
- Replaces World's Longest Floating Bridge










Project Location





How Do You Construct a Project and Protect Endangered Species?




Defined Fish Zones






Fish Zone #6

Species	Life History Stage	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec
Chinook	-Adult												
	-Residual												
	-Juvenile												
	-Adult												
Steelhead	-Residual												
	-Juvenile												
	-Adult												
Sockeye	-Juvenile Rearing												
	-Juvenile Out migrating												
Coho	-Adult												
	-Juvenile												
Bull Trout	-Sub Adult												










In-Water Work Activities

- Impact Pile Driving
- Drilled Shaft Template Pile Installation
- Drilled Shaft Casing Vibration
- Drilled Shaft Concrete Pour Within Casing
- Drilled Shaft Shaft Dewatering/Soil Excavation
- Pile Removal
- Above Water Work








Fish Zone #6: In-Water Work Activities

Driven Piles	950
Shaft Casings	125
Pile Removal	1180





Fish Zone #6: In-Water Work Windows

Construction Activity	Stone/Components	Proposed Work Window												
	Steps/Components	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec	
	Shoreline access													
Work Bridges Installation	Pile Driving				ı									
	Above water work													
	Template Piles/ Casing Vibration													
Drilled Shafts	Shaft dewatering/excavation													
·	Concrete pour w/in shaft													
Ex Br Removal	Above water work													
	Piling removal													
Work Bridges	Above water work													
Removal	Pile Removal													



Indicates No In-Water Work Permitted





Test Pile Project Objectives

Test Effectiveness of Noise Attenuation Methods

Determine the Feasibility of Removing Piles

Determine Lateral Load Characteristics of Soft

Soils







Test Locations







Other Benefits

- Barge Access to Shallow Water Areas
- Length, Capacity and Drivability of Piles
- Ability to Extract Piles
- Effectiveness of Noise Attenuation Devices








Summary of Noise Monitoring Results

Double Walled Noise Attenuation Pile (DNAP)


Minimal Reduction (4dB)





Summary of Noise Monitoring Results

Confined and Unconfined Bubble Curtains –
 20 to 30 dB Reductions











Effectiveness of Bubble Curtain












Bubble Curtain Noise Reduction



West Approach

Behavioral Threshold exceeded (150 dB), 96% Reduction

Injury Threshold exceeded (183/187 dB), 98% Reduction





In-Water Work Windows- Before Test

Construction Activity	Stana/Components	Proposed Work Window												
	Steps/Components	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec	
	Shoreline access													
Work Bridges Installation	Pile Driving													
	Above water work													
	Template Piles/ Casing Vibration													
Drilled Shafts	Shaft dewatering/excavation													
	Concrete pour w/in shaft													
Ex Br Removal	Above water work Piling removal													
Work Bridges Removal	Above water work													
	Pile Removal													



Indicates No In-Water Work Permitted





In-Water Work Windows- After Test

Construction Activity	Stone/Components	Proposed Work Window												
	Steps/Components	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec	
	Shoreline access													
Work Bridges Installation	Pile Driving													
	Above water work													
	Template Piles/ Casing Vibration													
Drilled Shafts	Shaft dewatering/excavation													
·	Concrete pour w/in shaft													
Ex Br Removal	Above water work Piling removal													
Work Bridges Removal	Above water work Pile Removal													



Indicates No In-Water Work Permitted






Noise Attenuation Summary

- The Fish Injury Threshold Reduces by 98%
- The Behavioral Fish Threshold Drops by 96%
- Significantly Reduced Mitigation for Affects on Fish
- Increased In-water Work Windows by 2 Months





Lateral Load Test








Depth of Embedment

Head Deflection (in)




Top of Shaft Deflection





Shaft Deflection








Moment Curve

Moment (kip-ft)







Lateral Load Test Summary

- Reduced deflections at top by 50%
- Reduced moments in shaft by 20%
- Reduced depth of embedment by 15%
- Reduced cost of shafts by 25%
- \$10M Savings







SR 520 Bridge Replacement Program

Test Pile Project Results

Questions

