

SELLWOOD BRIDGE

Project

MULTNOMAH COUNTY

The Shoo Fly

Sliding the Sellwood Bridge


September 2013

Presenters:

Kenneth Huntley, Scott Nettleton, Anthony Calcagno

Project Overview

Replace existing 88 year old bridge with new Steel Deck Truss Span



Existing Bridge
(looking north)

Heavy Cracking & Spalling




2004 Load Limit Change



West End Anchors added in the 60's



Column Twist



Building Encroaches on Bridge



Goals of “Shoo-Fly”

Provide Full Service Detour, Improved Safety, Speed Construction and Cost Savings



- Shoo-fly alignment options 1 and 2
- Shoo-fly alignment option 2 only

Approaches in Place Translated Truss



Option 1 Stage 1

Construct Main Span



Option 1 - Stage 2, East approach first stage Construction

Complete East Approach



Option 1 - Stage 3, East approach
second stage construction

Finish Demolition

<http://www.sellwoodbridge.org>





Finished Bridge,
Options 1 and 2

Challenges for Engineering the Sellwood Shoo Fly

- Split responsibilities
 - Contractor Engineer provided approach structural designs
- Site impacts
 - Condos on NE side
 - Coordination with City and Permitting
 - Communication of Intent to Permitting Agencies
- Technical
 - Foundations
 - River flow, scour and flood
 - Seismic
 - Wind
 - Staging
 - Connection to old structure

Foundations


Driving Frames and Vibratory Pile Installation



DESIGNER T. J. Greene	CONSTRUCTIVE CONSULTING AND CONSULTING ENGINEERS	TYLIN INTERNATIONAL engineers planners scientists	PROJECT NO. 21493	WILLAMETTE RIVER (SELLWOOD) BRIDGE SELLWOOD BRIDGE PROJECT OSWEGO HIGHWAY AND TACOMA ST.	SHEET 6 OF 41
DESIGNED BY Scott Harrison	MULTNOMAH COUNTY SEWER & WATER DIVISION		DATE Nov. 2011		DRAWN BY MICHAEL LEMONT
CHECKED BY Michael Lemont			DRAWN DATE		DETAIL NO. 7006-D-1
REVISION 1. Revised copy				DRIVING FRAME DETAILS 1	

River Flow, Scour and Flood

Where is the flow coming from?



Tidal influence causes most long term scour

River Flow, Scour and Flood

Modeling of Proposed Construction





Photo 3. Flood-Tide Design Event Result (All Structures)

River Flow, Scour and Flood



Extreme Event, Monitoring Installed



Seismic Design

Use of Existing Superstructure


Seismic Accelerations Reduced by 2.5 for Temporary Works



Transverse

Seismic Design

Use of Existing Superstructure



Longitudinal

Wind Loading

The Controlling Load

Period of Record...October 1940 - May 1999

Month	Climatic Averages		Extremes of Wind (1951-June 1999)								
	Dir.	Speed	Highest Avg.			Fastest Mile ²			Peak Wind Gust		
			Speed	Year	Dir.	Speed	Year	Dir.	Speed	Year	
Jan.	ESE	9.9	15.1	1995	S	54	1951	SW	63	1990	
Feb.	ESE	9.2	12.2	1993	SW	61	1958	S	68	1965	
March	ESE	8.3	10.9	1956	S	57	1963	S	71	1971	
April	NW	7.4	9.3	1981	S	60	1957	S	63	1972	
May	NW	7.1	8.6	1963	SW	42	1960	SW	48	1971	
June	NW	7.2	9.1	1974	SW	40	1958	SW	40	1994, '97	
July	NW	7.6	8.9	1962	SW	33	1983	SW	35	1983	
Aug.	NW	7.1	8.7	1966	SW	29	1961	E	38	1966	
Sept.	NW	6.5	8.0	1961	S	61	1963	SW	61	1963	
Oct.	ESE	6.5	8.4	1975	S	88	1962	S	104 ³	1962	
Nov.	ESE	8.6	11.2	1979	SW	56	1961	S	71	1981	
Dec.	ESE	9.5	12.9	1977	S	57	1951	S	74	1995 ⁴	
Annual	ESE	7.9	8.8	1995	S	88	Oct 1962	S	104 ³	Oct 1962	

WEST WIND LABORATORY, INC

761 Neeson Rd. #12, Marina, CA 93933 USA
 t 1.831.883.1533 f 1.831.883.1535
 www.westwindlaboratory.com e jraggett@westwindlaboratory.com

WIND STUDY
 WILLAMETTE RIVER TRANSIT BRIDGE
 PORTLAND, OREGON
 FINAL REPORT

for
 T. Y. Lin International

Job No. 10-03

9 August 2011

by

Jon D. Raggett, PhD, PE
 President, West Wind Laboratory, Inc.



exp 12/31/11

Historical Data, Comparison with Topography
 Conclusion - 65 MPH Design Wind Speed

Staging

Working Around Landslide Mitigation



Additionally, the bridge width and the existing bridge rail do not meet current standards for a detour bridge


Connections to Existing Material Properties, Geometry

Testing results are for Informational Purposes only.

Specimen number	CH-2-1	CH-2-2	CH-3-1	CH-3-2
Location (Top of Core Depth)	1'3" to 1'11"	2'7" to 3'3"	0'0" to 0'8"	1'11" to 2'7"
Date tested	05/27/08	05/27/08	05/27/08	05/27/08
Nominal Maximum Aggregate Size	1 ½"	1 ½"	1 ½"	1 ½"
Length of specimen prior to capping	7.13	7.20	7.21	7.21
Length of specimen after capping	7.25	7.32	7.33	7.39
Direction of load in respect to	P	P	P	P
Moisture condition at time of testing	Surface Dry	Surface Dry	Surface Dry	Surface Dry
Average diameter of core specimen	3.66	3.66	3.66	3.66
Length to diameter ratio (l/d) *	1.98	2.00	2.00	2.02
Applied load at specimen failure (lbs)	72961	80508	61293	73125
Specimen area (sq. in.)	10.52	10.52	10.52	10.52
Uncorrected unit psi	6935	7653	5826	6951
Strength correction factor *	---	---	---	---
Corrected unit psi (nearest 10 psi)	6940	7650	5830	6950

P - Perpendicular



*Specimen correction factor applied when length to diameter ratio falls below 1.8.





Information gathering, corrections at final Inspection

More Stuff

- Collision Fender
- Guard Rail Transition
- Piling Conflict Bent 17
- Support at Bent 21
- River Isolation
- Lighting




Truss Jacking System Layout on a Radius



Original design assumed single support track


Truss Translation Layout



Layout of translation path was critical

Truss Cradle Design


Support Bearing Across Skid Beams



Vertical plates in case of jack failure

Cradle Beam Challenges

Fitting Beams into Tight Spaces




Temporary Bearing

Steel Box Filled with Grout



Sides cut to fit irregular shape of the bearing casting


Truss chords unable to take load




Photos of the Slide




Photos of the Slide Cont.



Photos of the Slide Cont.



Photos of the Slide Cont.



Lessons Learned

- Leave a little extra space for field fit
- Coordination and planning paid off
 - Closure schedule was met
 - Opened 15 hours early
 - Public was well-informed = good press

Credits

Owner: Multnomah County

Engineers: T.Y. Lin International (*Main Span Bridge*)

CH2M HILL (*Roadway & Geotechnical*)

McGee Engineering (*Approach Bridge*)

Prime Contractor: Slayden-Sundt Joint Venture

Slide Subcontractor: Omega Morgan Inc.

Quick Facts:

Truss Length = 1,091 feet

Truss Weight = 3,400 Tons

Time to Slide = 13 hours

Any Questions

