

# CONTROLLING CRACKING AT THE ENDS OF PRETENSIONED CONCRETE BRIDGE BULB TEE GIRDERS

Pinar Okumus, Assistant Professor, State University of New York, Buffalo  
Michael G. Oliva, Professor, University of Wisconsin, Madison



THE UNIVERSITY  
of  
**WISCONSIN**  
MADISON

September 4–6, 2013  
Hyatt Regency Hotel | Bellevue, Washington

# PRE-TENSIONED BRIDGE GIRDERS



## *Advantages:*

- ✓ Durability
  - Crack free
  
- ✓ Structural Efficiency
  - span / depth up to 30
  - spans up to 200 ft
  
- ✓ Faster construction
  - Wider flanges
  - Fewer girders

# RESEARCH PROBLEM




## *Problem:*

- ✘ Cracks may form at plant
  - Corrosion
  - Higher maintenance and life cycle cost
  - Structural damage
  - Limits the use


# RESEARCH PROBLEM

- Survey among DOTs, precasters, consultants, researchers




# END REGION BEHAVIOR

- Crack formation
- Proximity to the load (prestress transfer)



# NONLINEAR ANALYSIS


- Analysis using Nonlinear Finite Element Analysis
- Experiments to verify simulations





# GIRDERS STUDIED

- Standard Wisconsin Bulb Tee Girders



# GIRDER END DETAILS



Steel prestressing strands




Steel reinforcing bars






# FEA MODEL - OVERVIEW

- Computational Efficiency
  - Symmetry
  - Nonlinearity limited to girder end



# FEA MODEL – MATERIAL PROPERTIES

- CONCRETE PROPERTIES: in tension



--- AASHTO LRFD	— FIB 2010
-----------------	------------

# HOW ACCURATE IS THE FEM?

*Embedded Gages in concrete*





*Surface Gages on rebar and strands*



*Measurements were taken at precast plants  
during de-tensioning*



# VERIFICATION BY EXPERIMENTS

- QUALITATIVE COMPARISON – Principal Tensile Strains



# VERIFICATION BY EXPERIMENTS


- QUANTITATIVE COMPARISON – Strain Change






# TYPICAL CRACKING

- CRACK CLASSIFICATION



# FEA RESULTS

- CONCRETE RESPONSE









# FEA RESULTS

- CONCRETE RESPONSE



*at the end*



*at transfer length*

***Principal Tension Strains***



# HOW CAN WE CONTROL CRACKING?



Rebar pattern



Strand de-bonding



Strand release order



Harped strand pattern




Location of lifting




# CRACK CONTROL BY REINFORCEMENT BARS

## TARGET CRACKS



**Horizontal web cracks**

# CRACK CONTROL BY REINFORCEMENT BARS



**Even #10 bars cannot prevent cracking (only 50% reduction)**

# HOW CAN WE CONTROL CRACKING?



Rebar pattern



Strand de-bonding



Strand release order




Harped strand pattern



Location of lifting

# CRACK CONTROL BY PARTIAL STRAND DEBONDING

10 ft  $\gg$  Transfer length  
↔







- *AASHTO limits debonding to 25% of total strands*
- *AASHTO does not provide specific guidance for debonded strand pattern*





# CRACK CONTROL BY PARTIAL STRAND DEBONDING






**Inclined and Y cracking can be eliminated**




# CRACK CONTROL BY PARTIAL STRAND DEBONDING

- DEBONDING PATTERN FOR Y CRACKS



# CRACK CONTROL BY PARTIAL STRAND DEBONDING


- IMPLEMENTATION




- **Strands should be distributed: Adjacent columns should not be debonded**
  - **Interior strands should remain bonded**

# CRACK CONTROL BY 12in STRAND DEBONDING

- Larger area to resist tension



# CRACK CONTROL BY 12in STRAND DEBONDING



**Comparable to 35% debonding, web cracks can be limited  
Y cracks can be eliminated**



# HOW CAN WE CONTROL CRACKING?



Rebar pattern



Strand de-bonding



Strand release order




Harped strand pattern




Location of lifting



# CRACK CONTROL BY STRAND CUTTING ORDER




*Exterior strands first*



*Interior strands first*

# CRACK CONTROL BY STRAND CUTTING ORDER

- Increase in strains during de-tensioning



**Smaller strains if internal strands are cut first or all cut simultaneously**

# HOW CAN WE CONTROL CRACKING?



Rebar pattern



Strand de-bonding



Strand release order




Harped strand pattern




Location of lifting

# CRACK CONTROL BY DRAPED STRANDS

- TARGET CRACKS



# CRACK CONTROL BY DRAPED STRANDS



**Lowering and spreading draped strands can eliminate inclined cracking but... by compromising girder efficiency**



# HOW CAN WE CONTROL CRACKING?



Rebar pattern



Strand de-bonding



Strand release order



Harped strand pattern




Location of lifting




# CRACK CONTROL BY LIFTING LOCATION

- TARGET CRACKS




# CRACK CONTROL BY LIFTING LOCATION



*Inclined and web cracks grow significantly*

# CRACK CONTROL BY LIFTING LOCATION


- LIFTING LOCATION



***Girders should be lifted as close to the end as possible  
Lift locations should not be in nonlinear region***

# KEY FINDINGS

Control Method			Inclined Cracks	Web Cracks	Y Cracks
1	Increase in	The closest two bars to girder			
2	Area of:	Bars further away from the girder			
4	Debonding Some Strands at the End				
5	Debonding All Strands for 12in from the E				
6	Change in Strand Cutting Order				
9	Lowered & Spread Draped Strands				



**HIGH** = can eliminate cracking

**MODERATE** = can reduce strains significantly

# Acknowledgements





**Thank you  
Questions?**