

Incorporating Innovative Materials into a Seattle, WA Bridge to Improve Seismic Resilience

Shape Memory Alloy and Engineered Cementitious Composite

Jed Bingle PE, SE
Washington State Department of Transportation
Bridge and Structures Office

Western Bridge Engineer's Seminar
Portland, Oregon
September 7, 2017

Presentation Outline

- Shape Memory Alloy (SMA) and Engineered Cementitious Composite (ECC)
 - Current Seismic Bridge Design Philosophy
 - Improving Seismic Bridge Design with Innovative Materials
 - Examples of Research Results
 - Implementation SMA and ECC into a WSDOT Bridge

Current Seismic Design Philosophy

Primary Seismic Performance Objective:
Collapse Prevention



“Failure”

Current Seismic Design Philosophy

Primary Seismic Performance Objective:
Collapse Prevention



“Failure”

Photo: H.G. Wilshire, U.S.G.S.

Current Seismic Design Philosophy

Primary Seismic Performance Objective:
Collapse Prevention



“Failure”

Photo: Caltrans

Current Seismic Design Philosophy

- May result in bridge closures
 - Excessive column damage
 - Excessive lateral deflection
 - Limited access; may or may not allow emergency response vehicles
- Extensive Repairs
 - Patching of spalled concrete
 - Shoring of spans
 - Replacement
- Economic Impacts
 - Disrupts public transportation
 - Major economic impact



Current Seismic Design Philosophy

Primary Seismic Performance Objective:
Collapse Prevention



“Success”

Photo: PEQIT

Current Seismic Design Philosophy

Primary Seismic Performance Objective:
Collapse Prevention



“Success”

Current Seismic Design Philosophy

Primary Seismic Performance Objective:
Collapse Prevention



Photo: MCEER



“Success”

Photo: WSDOT

Improve Seismic Design


- Define Performance Based Design
 - Keep bridges operational
 - Minimize repair needs
 - Minimize residual drift
 - Reduce damage to the plastic hinges
 - Maintain an energy dissipation system

Innovative Materials

- Shape Memory Alloy Bars (SMA)



- Engineered Cementitious Composite (ECC)




Innovative Materials SMA


- Shape Memory Alloy Bars (SMA)
 - Nickel-Titanium or Copper-Aluminum-Manganese
 - Superelastic




Conventional Material Steel



Innovative Materials SMA



Innovative Materials SMA





Spliced SMA into Column Cage




Innovative Materials ECC

- Engineered Cementitious Composite (ECC)
 - Cement, Sand, Fly Ash and Polyvinyl Alcohol Fibers
 - Reduce damage to hinge



Innovative Materials Bridge Research



- 1/4 Scale, 4 Span Bridge, Total Length=110ft
- Innovative Materials in Bottom Plastic Hinges
- Conventional RC in Top Plastic Hinges




University of Nevada, Reno



Innovative Materials Bridge Research

Residual Damage After 10% Drift



Conventional

SMA/Conc.

SMA/ECC

Innovative Materials Bridge Research

- SR99-RC: Conventional RC Reference Model
- SR99-LSE: Long SMA with ECC Column
- SR99-SSE: Short SMA with ECC Column



Innovative Materials Bridge Research

- Three - 0.3 Scale Columns
 - 2 Incorporating SMA and ECC
 - 1 Conventional RC
- 62 in clear height
- 18 in x 18 in cross section
- Reversed cyclic loading




Innovative Materials Bridge Research

Damage at End of Testing



SR99-RC (8% Drift)




SR99-LSE (12% Drift)



SR99-SSE (10% Drift)

Innovative Materials Bridge Research

Measured Residual Drift Ratios




SR 99 South Access – NB Off Ramp

- Owner: Washington State Department of Transportation
- Engineer: Washington State Department of Transportation
- Contractor: Interwest Construction Inc.




SR 99 South Access - NB Off Ramp




SR 99 South Access – NB Off Ramp

- Three Spans (110ft; 180ft, 110ft)
- Precast Post-Tensioned Splice Tub Girder
- Single Column Piers
- Square Columns (5ft x 5ft) w/ Circular Core
- ECC Top 5ft of Column





SR 99 South Access – NB Off Ramp


- Limitation of research funding
- Shape Memory Alloy used in hinges at top of column
- Approximately 50 ft. liquefiable soil below existing ground line
- Seismic demand is greatest at the top of the column



SR 99 South Access – NB Off Ramp Construction Photos



SR 99 South Access – NB Off Ramp Construction Photos



SR 99 South Access – NB Off Ramp

- Challenges with including SMA
 - Cost
 - ASTM A706 = \$1 / lb. (installed)
 - SMA = \$92 / lb. (delivered)
 - Schedule – 6 month delivery, not including process to head bar for mechanical splice
 - Mechanical splice required in hinge region




SR 99 South Access – NB Off Ramp

- Challenges with including ECC
 - Production rate
 - 10 to 12 ft³ / batch
 - Total 125 ft³ each column
 - One shift per column



SR 99 South Access – NB Off Ramp

- Challenges with including ECC
 - Curing temperature
 - Maximum temperature per Spec. 165 °F
 - w/ Cooling System



Questions?



Jed Bingle PE, SE
Washington State DOT
Bridge and Structures Office
(360) 705-7222
binglej@wsdot.wa.gov