


TYLin

2023 Western Bridge Engineer's Seminar

How to Lengthen an Existing Bridge Span



Project Team



JOINT
VENTURE

Coffman Ames Joint Venture

DESIGN
TEAM

TYLin

AECOM

Kimley»»Horn

Expect More. Experience Better.

 **Terracon**

Site Location

SR 101L, I-17 TO
PRINCESS DR






15th Avenue UP


- Idea: How to lengthen a span?
- Alternate Technical Concept - ATC
 - Dimension Changes
 - Metric to English Lanes
 - Sidewalk 4.92 ft to 6.00 ft
 - Design Specification
 - Existing Bridge: AASHTO Std Specifications 17th Edition 2002
 - New Bridge: AASHTO LRFD Bridge Design Specifications, 8th Edition
 - Allowable Tension in Existing Bridge
 - 179 psi to 256 psi
 - AASHTO allowable 402 psi
 - Requested use of $4 \sqrt{f'c}$ or 268 psi

15th Avenue UP




15th Avenue UP

HINGE DETAIL



15th Avenue UP

P/S BARS





15th Avenue UP

CHANGES FROM PURSUIT

- Hinge Connection Changed
 - Top Corbel Connection Changed to Full Depth Connection
 - Added Bottom P/S Bars with Dowels
 - Existing Span increased from 3.00 feet to 4.77 feet
 - Tension increased from 179 psi to 256 psi to 300 psi
- Wall Changed
 - Soil Nail Wall Changed to Cast-in-Place Pier Wall
- End Span Changes
 - Frame 2 End Span increased to 25 feet




15th Avenue UP

DESIGN ISSUES

- Conversion of Existing Metric to English
- Shallow Superstructure Depth (3.94 feet)
 - Hinge Design
 - Construction Access
- Use of Two Design Specifications
 - Existing: Standard Specifications 17th Edition 2002
 - New: LRFD Bridge Design Specifications, 8th Edition
- Traffic Access on Frontage Road
- Existing Abutment Wall Strength

15th Avenue UP


PLAN



LOCATION PLAN
New C. I. P. Post-tensioned Box Girder Bridge Extension


15th Avenue UP

BRIDGE FLARE



15th Avenue UP

ELEVATION




ELEVATION

15th Avenue UP


Location	Span (feet)	Depth (feet)	Width (feet)	Structure Type
Back Span 1	20.00	5.00	56.71	Box Girder
Overhang	8.45	5.00	63.00	Solid
Existing Span 2	90.55	3.94	63.00	Box Girder
Existing Span 3	90.55	3.94	63.00	Box Girder
Overhang	21.11	Varies: 5.0 to 6.0	63.00	Box Girder
Back Span 4	25.00	6.00	56.71	Box Girder

15th Avenue UP

TYPICAL SECTION



TYPICAL SECTION AT PIER
Scale: 3/16" = 1'-0




15th Avenue UP

	Number Shafts	Diameter (inch)	Depth (feet)	Service Load Uplift (Kips)	Service Load Down (Kips)	Strength Load Uplift (Kips)	Strength Load Down (kips)
Abutment 1	3	48	35.0	-228	206	-338	328
Pier 1	4	60	41.0		869		1170
Pier 3	4	60	48.5		1109		1496
Abutment 2	4	48	35.5	-287	135	-379	175

15th Avenue UP


FRAME 1

- Web Spacing
- DS Location
- Solid Span
- Flare
- Width Change





15th Avenue UP

FRAME 2



15th Avenue UP

FRAME 1




15th Avenue UP

	Frame 1	Frame 2	
Pjack	7031	16,874	kips
Number Strands	160	384	(0.6" Dia.)
Strands	20	48	Per web
Duct Ties	Yes	No	
f'c Deck	3.5	3.5	ksi
f'c Web	3.5	4.0	ksi


15th Avenue UP

HINGE - Between Webs




15th Avenue UP

HINGE – Near Webs




15th Avenue UP

HINGE - Section



15th Avenue UP

HINGE




PARTIAL PLAN P/S BAR AT HINGE 1
Scale: 1/2" = 1'-0"

Ends shall be Protected from Corrosion per Manufacturer Recommendation. Detail to be submitted to Engineer for review and approval.


15th Avenue UP

HINGE



15th Avenue UP

HINGE




15th Avenue UP

Item	
Prestress Bar	Type 2 Deformed
Size	1 3/8" Diameter
Area Bar	1.58 sq inch
fpu	150 ksi
Jacking	0.70 fpu
Pjack Force	5309 kips per Frame


15th Avenue UP

EXISTING




15th Avenue UP

STAGE I » *Step 1*




15th Avenue UP

STAGE I » *Step 2*




15th Avenue UP

STAGE I » *Step 3*




15th Avenue UP

STAGE I » *Step 4*



15th Avenue UP


STAGE II » Step 1



15th Avenue UP


STAGE II » *Step 2*

② Remove Backwall & Expansion Joint




15th Avenue UP

STAGE II » *Step 3*




15th Avenue UP

STAGE II » *Step 4*




15th Avenue UP

STAGE II » *Step 5*




15th Avenue UP

STAGE II » *Step 6*




15th Avenue UP

STAGE II » *Step 7*




15th Avenue UP

STAGE III » *Step 1*




15th Avenue UP

STAGE III » *Step 2*




15th Avenue UP

STAGE III » *Step 3*




15th Avenue UP

STAGE III » *Step 4*




15th Avenue UP

STAGE III » *Step 5*




15th Avenue UP

STAGE III » *Step 6*




15th Avenue UP

STAGE III » *Step 7*




15th Avenue UP

STAGE III » *Step 8*




15th Avenue UP

STAGE IV » *Step 1*



15th Avenue UP


STAGE IV » *Step 2*



15th Avenue UP


STAGE IV » *Step 3*

③ Construct Sidewalk, Parapet, Railing & Fence



15th Avenue UP

STAGE IV » *Step 4*





15th Avenue UP

- FHWA Field Inspection
- Request to Review Plans and Calculations
- Questioned Lack of Strut-and-Tie Analysis
- Performed Analysis
- **RESULT:**
 - No changes to any rebar size
 - No changes to any location
 - FHWA Questioned lack of Supplemental Reinforcement

15th Avenue UP

5.8.2.5.3a – General

The limiting compressive stress at the node face, f_{cu} , shall be taken as:

$$f_{cu} = m v f'_c$$

v = concrete efficiency factor:

- 0.45 for structures that do not contain crack control reinforcement
- As shown in Table 5.8.2.5.3a-1

5.8.6.3 – Crack Control Reinforcement

Structures which have been designed using the efficiency factor of Table 5.8.2.5.3a-1 shall contain orthogonal grids of bonded reinforcement.

$$A_v = 0.003 * b_w * s_h$$




Table 5.8.2.5.3a-1—Efficiency Factors for Nodes with Crack Control Reinforcement

Face	Node Type		
	CCC	CCT	CTT
Bearing Face	0.85	0.70	$0.85 - \frac{f'_c}{20 \text{ ksi}}$
Back Face			
Strut-to-Node Interface	$0.45 \leq v \leq 0.65$	$0.45 \leq v \leq 0.65$	$0.45 \leq v \leq 0.65$



15th Avenue UP

- ADOT Policy Status
- Proposal to Study When/Where Analysis Method Used

15th Ave UP

SHORING & APPROACH WALLS




15th Ave UP

RETAINING WALL



15th Ave UP

WALLS



15th Ave UP

BACK SPAN



15th Ave UP

WEB FORMS




15th Ave UP

END SPAN
ABUTMENT
CAP
ROOM TO
PULL



15th Ave UP

BOTOM SLAB
& WEB POUR




15th Ave UP

DECK REINFORCING



15th Ave UP

DECK POUR



15th Ave UP



15th Ave UP

HINGE



15th Ave UP

ACCESS HOLES
JACKING



15th Ave UP

JACKING

ANALYSIS

EXISTING

ABUTMENT CAP



15th Ave UP

EXISTING CELL



15th Ave UP

INSIDE CELL



15th Ave UP




15th Ave UP

HINGE DETAILS



15th Ave UP




15th Ave UP

P/S BAR DUCTS



15th Ave UP

PRESTRESS JACKING



15th Ave UP

ABUTMENT REMOVAL



15th Ave UP

LOOKING
NORTH



15th Ave UP

EXPANSION JOINT



15th Ave UP

LOOKING
SOUTH



15th Ave UP

LOOKING
SOUTH



TYLin

2023 Western Bridge Engineer's Seminar

Questions?

