

# Cloverdale Bridge Replacement



Mike Johnson, Idaho Transportation Department, Bridge Section

Your Safety. Your Mobility. Your Economic Opportunity



# Cloverdale Bridge Replacement



Mike Johnson, Idaho Transportation Department, Bridge Section

Your Safety. Your Mobility. Your Economic Opportunity



# Cloverdale Bridge Replacement



Mike Johnson, Idaho Transportation Department, Bridge Section




Your Safety. Your Mobility. Your Economic Opportunity

# Cloverdale Bridge Replacement



Mike Johnson, Idaho Transportation Department, Bridge Section



Your Safety. Your Mobility. Your Economic Opportunity


# Cloverdale Bridge Replacement



Your Safety. Your Mobility. Your Economic Opportunity


# Site Overview

**Cloverdale GS**



Your Safety. Your Mobility. Your Economic Opportunity

# Site Overview



Your Safety. Your Mobility. Your Economic Opportunity

# Bridge History Prior to June 2018



Your Safety. Your Mobility. Your Economic Opportunity



# Overheight Load Damage - 2002



Your Safety. Your Mobility. Your Economic Opportunity

# Overheight Load Damage - 2006



Your Safety. Your Mobility. Your Economic Opportunity

# Overheight Load Damage - 2016



Your Safety. Your Mobility. Your Economic Opportunity

June 16, 2018



Your Safety. Your Mobility. Your Economic Opportunity

June 16, 2018



<https://www.ktvb.com>




Your Safety. Your Mobility. Your Economic Opportunity

# The Damage



Your Safety. Your Mobility. Your Economic Opportunity

# Condition Assessment



Your Safety. Your Mobility. Your Economic Opportunity


Table 1: Physical Effects of Temperature on Concrete <sup>[8]</sup>

Temperature	Color Change	Changes in Physical Appearance and Benchmark Temperatures	Concrete Condition
0 to 550 °F (0 to 290 °C)	None	Unaffected	Unaffected
550 to 1100 °F (290 to 590 °C)	Pink to red	Surface crazing: 570 °F (300 °C); Deep cracking: 1020 °F (550 °C); Popouts over chert or quartz aggregate: 1070 °F (575 °C)	Sound but strength significantly reduced
1100 to 1740 °F (590 to 950 °C)	Whitish Grey	Spalling, exposing not more than 25% of reinforcing bar surface: 1470 °F (800 °C); Powdered, light colored, dehydrated paste: 1650 °F (575 °C)	Weak and friable
1740+ °F (950+ °C)	Buff	Extensive spalling	Weak and friable





# Condition Assessment



Your Safety. Your Mobility. Your Economic Opportunity

# Decision to Repair or Replace



Your Safety. Your Mobility. Your Economic Opportunity

# Decision to Repair or Replace

## Inspection and Repair of a Fire Damaged Prestressed Girder Bridge

RICHARD STODDARD, Washington State DOT, Olympia, WA

IBC-04-17

RICHARD S. STODDARD, P.E. 98 - 2804 IBC

### Section 1 Incident Response

DAMAGE INSPECTION REPORT 12/12/02

On December 11, 2002, at approximately 4:00 pm, a railroad tanker collision caused a fire under a prestressed girder bridge that consumed 30,000 gallons of methanol, (photo 1). This section of the bridge was a relatively new continuous three span frame constructed in 1997. The girders had a span length of 146 feet, a 28 day concrete strength of 7000 psi, and 0.5" diameter 270 ksi steel strands. The bridge deck and columns were constructed using 5000 psi concrete and 60 ksi mild steel. Confinement reinforcement in the columns was provided by tightly wound spiral cages.



Photo 1. Puyallup River Bridge Railroad Tanker Fire

The fire engulfed Span 8 and maintained a high flame temperature for approximately one hour. The interstate freeway was immediately closed to traffic and remained closed pending an all night structural inspection. The bridge displayed no unusual deflections or misalignments and was reopened to commuter traffic and legal weight trucks on the morning of December 12<sup>th</sup>. Over weight trucks were prohibited and routed to I-5.

## JOINT TRANSPORTATION RESEARCH PROGRAM

INDIANA DEPARTMENT OF TRANSPORTATION AND PURDUE UNIVERSITY



## Post-Fire Assessment of Prestressed Concrete Bridges in Indiana



Amit H. Varma, Jan Olek, Christopher S. Williams, Tzu-Chun Tseng, Sijia Wang, Dan Huang, Tom Bradt

SPR-4221 • Report Number: FHWA/IN/JTRP-2021/05 • DOI: 10.5703/1288284317290



Your Safety. Your Mobility. Your Economic Opportunity

# Required Collaboration of Several Agencies to Complete the Project so Quickly



- Date of Accident – June 16, 2018
- Decision to Replace and Move Forward – June 27, 2018
- Design Plans, Schedule, and Estimate Complete (PS&E) - October 1, 2018
- Construction Contract Awarded – November 5, 2018



# I-84 Corridor Traffic



Your Safety. Your Mobility. Your Economic Opportunity



# Cloverdale Corridor Plan





<https://www.achdidaho.org>

Franklin Rd.





Your Safety. Your Mobility. Your Economic Opportunity



96'-0" SPAN 1

96'-0" SPAN 2


77'-0" OUT TO OUT



Your Safety. Your Mobility. Your Economic Opportunity




Precast Deck Bulb-Tee




MINIMUM VERTICAL  
CLEARANCE = 17.5'

Precast Columns /  
Cap Beam







Your Safety. Your Mobility. Your Economic Opportunity




Your Safety. Your Mobility. Your Economic Opportunity




PRESTRESS FORCE ~ KIPS		CONCRETE STRENGTH ~ PSI			
FINAL AFTER LOSSES	INITIAL BEFORE LOSSES	AT RELEASE $f'_{ci}$	AT 28 DAYS $f'_c$	(A)	(B)
1205	1582	7000	8000	96'-3"	94'-11"
1205	1582	7000	8000	96'-3"	94'-11"



Your Safety. Your Mobility. Your Economic Opportunity



SECTION AT ABUTMENTS




Your Safety. Your Mobility. Your Economic Opportunity

# Bridge Demolition – December 3, 2018



Your Safety. Your Mobility. Your Economic Opportunity

# Detour Routes



## I-84, Cloverdale Rd. Overpass Reconstruction Detour Routes

-  Westbound Detour Route
-  Eastbound Detour Route
-  Both East & Westbound



<https://www.achdidaho.org>



Your Safety. Your Mobility. Your Economic Opportunity

## Pile Driving Challenges

- Power Lines
- Gas Line



Your Safety. Your Mobility. Your Economic Opportunity





# Column Delivery





Your Safety. Your Mobility. Your Economic Opportunity

# Column Delivery



# Pier Cap Delivery



Your Safety. Your Mobility. Your Economic Opportunity

# New Precast Pier Column Detail



Your Safety. Your Mobility. Your Economic Opportunity






# Pier Cap Closure Pour



Your Safety. Your Mobility. Your Economic Opportunity



# Girders at Forterra



11. INTERFACE OF PRECAST CONCRETE COMPONENTS SHALL BE INTENTIONALLY ROUGHENED THROUGH THE USE OF A CHEMICAL RETARDER APPLIED TO THE PRECAST COMPONENT FORMWORK. THE MATERIAL SPECIFICATIONS OF THE CHEMICAL RETARDER SHALL BE SUBMITTED FOR THE ENGINEER'S REVIEW AND APPROVAL.
12. AMPLITUDE OF ETCH SHALL BE AT LEAST 0.25" AND NO LARGER THAN 1/2 THE NOMINAL COARSE AGGREGATE SIZE OF THE PRECAST COMPONENT CONCRETE.
13. THE PRECAST FABRICATOR IS NOT ALLOWED TO USE SANDBLASTING, ABRADING, OR A FORM LINER TO CREATE AN EXPOSED AGGREGATE SURFACE.



# Girder Delivery



Your Safety. Your Mobility. Your Economic Opportunity

# Girder Delivery



Your Safety. Your Mobility. Your Economic Opportunity





# Girder Equalization



Your Safety. Your Mobility. Your Economic Opportunity

# Girder Equalization



Your Safety. Your Mobility. Your Economic Opportunity

# UHPC Girder Connection



Your Safety. Your Mobility. Your Economic Opportunity

# PPC Overlay



**Your Safety. Your Mobility. Your Economic Opportunity**



# Interstate Traffic Fully Open – July 2, 2019



Your Safety. Your Mobility. Your Economic Opportunity



# Construction Continues on Local Road– July 2019



Your Safety. Your Mobility. Your Economic Opportunity

# Project Substantially Complete – August 23, 2019



Your Safety. Your Mobility. Your Economic Opportunity



Your Safety. Your Mobility. Your Economic Opportunity

