

DETAIL

EXPLODED VIEW
BREAKAWAY BASE CONNECTOR
(SEE NOTE 1)

NOTES:


- See Standard Specification Section 9-06.16 for Breakaway Base Connection details.
 Dimensions for the parts used to assemble the base connections are intentionally not shown.
 Base connections are patented manufactured products that are in compliance with NCHRP 350 crash test criteria. The Breakaway Base Connection details are only shown on this plan to illustrate how parts are assembled.
- 2. See **Standard Plan J-20.26** for Accessible Pedestrian Pushbutton (APS) details; Audible Information Device (AID) pedestrian pushbutton similar.
- 3. Secure conductor in adjacent Junction Box per detail in Standard Plan J-28.70.
- 4. Where shown in the plans, install plaque (R10-32P) "PUSH BUTTON FOR 2 SECONDS FOR EXTRA CROSSING TIME" above the Accessible Pedestrian Signal (APS) assembly. Add 14" (in) to post height to accommodate plaque and leave a 2" (in) space between signs.
- 5. Mounting distances vary between manufacturers. See manufacturer's recommendations for mounting information.
- 6. Junction Box serving the Standard shall preferably be located 5' 0" (10' 0" Max.) from the Standard.
- 7. Two button installation may require adaptor(s) or extension(s).
- 8. Pushbutton height is measured from the walking surface to the center of the actual pushbutton circle.




PEDESTRIAN PUSHBUTTON (PPB) POST AND FOUNDATION STANDARD PLAN J-20.15-04


SHEET 1 OF 2 SHEETS






FLAT FOUNDATION DETAIL ELEVATION VIEW







FLAT FOUNDATION PERSPECTIVE VIEW




CURB FOUNDATION PLAN VIEW





CURB FOUNDATION PERSPECTIVE VIEW (SKIRT NOT SHOWN)



PEDESTRIAN PUSHBUTTON (PPB) POST AND FOUNDATION STANDARD PLAN J-20.15-04

SHEET 2 OF 2 SHEETS

